

iRANGER



Key Features:

1. Up to 8 channel cameras with 720p realtime preview
2. H.264 dual-stream video compression
3. All channel 720P
4. HD MI / VGA simultaneous video output
5. 4 channel synchronous realtime playback, GRID interface & smart search
6. Support 1 SATA HDD up to 4TB, 2 USB2.0
7. Multiple network monitoring: Web viewer, CMS & XMEYE

Specification

System	Main processor	His3521
Video	video compression	H.264(High Profile);
	Encode	8*720P real-time
	Decode	8*720P real-time
	Multi-mode input	AHD-M:8*720P; AHD-L:8*960H(analog) AHD-M:8*720P; +4*IPC720P 2*IPC1080P+2*IPC720P 8*IPC720P
Audio	Audio compression	G.711A
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4*720P@25fps)
Storage and backup	Space occupation	960H:12~20G/ day*channel 720P:20G~30G/ day*channel audio:691.2M/ day*channel
	Backup mode	Network backup,USB HDD, USB writer,SATA writer
Interface	Video input	8 BNC
	Video output	1ch VGA,1ch HD MI
	Audio input	4ch RCA
	Audio output	1ch RCA
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	One RS485;support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA(Each maximum support 4T)
Other	Power	12V/2A
	dimension	255mm(length)* 225mm(width)* 60mm(height)

